

# Alumicool

## A BITUMEN BASED REFLECTIVE PAINT

### KEY BENEFITS

- Easy to apply
- Protects bituminous surfaces
- Reduces surface temperatures
- Will not contaminate drinking water

## PRODUCT INFORMATION

### DESCRIPTION

Alumicool in an economical bitumen based aluminium paint suitable for almost any surface. Alumicool dries to a bright silver and reflects the sun's rays, reducing inside temperatures by as much as 8OC. Alumicool retards corrosion and protects against further deterioration. Will not contaminate drinking water. Dries in 12-18 hours.

### USAGE/PURPOSE

Ideally suited as:

- a protective, reflective coating for all bituminous roofing membranes including Malthoid.
- a protective coating for galvanised roofs, exteriors of water and storage tanks(above and below ground)
- a protective coating for exposed metal structures including above ground pipelines, windmills and all metal surfaces. can also be used to overpaint Bitumen Paint, Brushable Hydroseal and Heavy Grade Hydroseal.

### PACKAGING

1 litre, 4 litre and 20 litre containers

## TECHNICAL INFORMATION

### CHARACTERISTICS

Colour:	Silver
Dry Time:	12 - 24 hours
Flammability:	Flammable - Flash point 32°C
Coverage:	On bituminous surfaces: 7m <sup>2</sup> /litre approx. On metal surfaces: 8-10m <sup>2</sup> /litre approx.
Weight:	1kg/litre approx.

## USAGE GUIDELINES

### SURFACE PREPARATION

All surfaces must be free from oils, grease, wax, dust and any loose or contaminating materials. Remove all rust prior to application and repair where necessary. New galvanised iron must be allowed to weather for at least six months prior to application. Allow 14 days exposure of bituminous surfaces or membranes before coating with Alumicool.

### APPLICATION

Mix the contents of the container thoroughly before use. Apply by brush, roller or spray. To prevent settling, it may be necessary to stir occasionally during application. During application, allow the Alumicool to flow on to the surface from the brush. **DO NOT BRUSH OUT OR OVERWORK.** Apply coating in one direction.

### PRIMER

A primer is not required for normal application of Alumicool. Simply apply two coats - the first will act as a primer and the second as a top coat. Allow 24hours between coats.

### CLEAN UP

Thoroughly clean brushes and rollers in mineral turps and rinse under water. Clean spray equipment with mineral turps.

### PRECAUTIONS

Material Safety Data Sheet must be read and understood prior to use.

### STORAGE

Store in sealed containers under cover at normal temperatures for 12 months

### TECHNICAL SERVICE

TREMCO has a team of qualified Technical Sales Representatives who provide assistance in the selection and specifications of products. For more detailed information or service and advice call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

### GUARANTEE/WARRANTY

We warrant our products to be free of defects and manufactured to meet published physical properties when tested according to applicable specifications and TREMCO standards.

Under this warranty we will provide at no charge, product to replace any product proven to be defective when applied in accordance with our written instructions and in applications recommended by TREMCO as being suitable for this product.

All claims concerning product defects must be made within 12 months of shipment. Absence of such claims in writing during this period will contribute a waiver of all claims with respect to such product. This warranty is in lieu of any and all other warranties expressed or implied.