

Bitumen Paint

A BITUMEN, SOLVENT BASED PAINT

Key Benefits Summary

- Good water, acid and alkali resistance.
- Suitable for protection of galvanised iron gutters, downpipes, metal railings and metals exposed to weather, for priming dry concrete decks and as an adhesive to adhere Malthoid to metal.

PRODUCT INFORMATION

DESCRIPTION

Bitumen Paint is a bitumen, solvent based paint with good water, acid and alkali resistance.

USAGE/PURPOSE

Ideally suited for:

- protection of galvanised iron gutters, downpipes, metal railings and metals exposed to weather
- priming dry concrete decks
- an adhesive to adhere to Malthoid to metal

PACKAGING

20 Litre Containers

TECHNICAL INFORMATION

CHARACTERISTICS

Colour: Black
Dry Time: 12-24 Hours
Flashpoint: Flammable - Flash point 32oC min
Coverage: As a paint/primer:
8m²/litre approx. on concrete
10m²/litre approx. on metal
As an adhesive for Malthoid:
5m²/litre approx.
Net Weight: 1Kg/litre approx.
Storage: May be stored in sealed containers under cover at normal temperatures for 12 months.

USAGE GUIDELINES

SURFACE PREPARATION

All surfaces must be thoroughly clean, dry, sound and free from grease, oils, waxes and all loose materials.

New galvanised iron must be allowed to weather for at least six months prior to application.

APPLICATION

When used as a protective coating, use directly from the container with a brush, broom or spray (55kPa pressure in pot and 275kPa pressure at gun). When used as an adhesive for Malthoid, first loose lay Malthoid in position. Turn back the layer (approx. half way), paint the exposed metal with Bitumen Paint, then apply a coating of Bitumen Paint to the underside of the Malthoid. Place the sheet in position again and rub out to remove air pockets. Repeat this operation with the remainder of the sheet. To provide increased durability in external application, allow to dry for 14 days and apply a reflective paint, eg Tremco Alumicool, Tennis Court Paint etc.

CLEAN UP

Clean tools and equipment with mineral turps.

STORAGE

Store in sealed containers under cover at normal temperatures for 12 months. Containers must be kept sealed at all times when the material is not being used.

TECHNICAL SERVICE

TREMCO has a team of qualified Technical Sales Representatives who provide assistance in the selection and specifications of products. For more detailed information or service and advice call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

GUARANTEE/WARRANTY

We warrant our products to be free of defects and manufactured to meet published physical properties when tested according to applicable specifications and TREMCO standards.

Under this warranty we will provide at no charge, product to replace any product proven to be defective when applied in accordance with our written instructions and in applications recommended by TREMCO as being suitable for this product.

All claims concerning product defects must be made within 12 months of shipment. Absence of such claims in writing during this period will contribute a waiver of all claims with respect to such product. This warranty is in lieu of any and all other warranties expressed or implied.