

Builders Adhesive

HIGH STRENGTH FLEXIBLE GENERAL PURPOSE SEALANT

Key Benefits Summary

- Versatile adhesive, developed for bonding most common materials used in the construction industry.
- Tough, high solids adhesive that gives a flexible glue base.
- May be used in many home repair applications.

PRODUCT INFORMATION

DESCRIPTION

TREMCO® Builders Adhesive is a versatile adhesive, developed for bonding most common materials used in the construction industry. These include timber, masonry, brick, galvanised iron, steel and polystyrene foam.

TREMCO® Builders Adhesive is a tough, high solids adhesive that gives a flexible glue base. It is suitable for use in sheet flooring and wall panelling. It may also be used in many home repair applications.

USAGE/PURPOSE

- Bonding most common construction materials.

COLOUR

- Beige

PACKAGING

- 300ml and 850ml (920g) cartridge

TECHNICAL INFORMATION

CHARACTERISTICS

- SOLIDS 74% by weight
- FLASHPOINT -18°C
- SPECIFIC GRAVITY 1.09 ± 3%

(Note: Typical properties should not be used as specifications).

TREMCO PTY LTD ABN 25 000 024 064
Unit 1, 2 Park Rd, RYDALMERE NSW 2116 Australia
Tel: (02) 9638 2755 Fax: (02) 9638 2955
tremco@tremco.com.au

USAGE GUIDELINES

APPLICATION

All surfaces must be clean and dry. Apply adhesives to prepared surfaces - press surfaces together and hold securely. For fast setting bonds, separate surfaces for 2-5 minutes - reposition and press in place. Temporary fastening is not normally required when fixing lightweight materials such as polystyrene foam. Manufacturer's nailing instructions should be followed when fixing sheet flooring.

DRYING TIME

Initial bond in 1-30 minutes. Handling strength in 30 minutes to 24 hours. All drying times are dependant on porosity of materials plus ambient temperature.

HEALTH AND SAFETY PRECAUTIONS

- Avoid contact with skin, eyes and mouth and avoid breathing vapour.
- Keep away from flame and sources of ignition.
- Keep container closed when not in use.

STORAGE

Store in original unopened packaging in dry conditions between +5°C and +25°C.

SHELF LIFE

12 months when stored in its original unopened packaging.

TECHNICAL SERVICE

TREMCO has a team of qualified Technical Sales Representatives who provide assistance in the selection and specifications of products. For more detailed information or service and advice call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

GUARANTEE/WARRANTY

We warrant our products to be free of defects and manufactured to meet published physical properties when tested according to applicable specifications and TREMCO standards.

Under this warranty we will provide at no charge, product to replace any product proven to be defective when applied in accordance with our written instructions and in applications recommended by TREMCO as being suitable for this product.

All claims concerning product defects must be made within 12 months of shipment. Absence of such claims in writing during this period will contribute a waiver of all claims with respect to such product. This warranty is in lieu of any and all other warranties expressed or implied.