

Flashpatch

SELF ADHESIVE COLD APPLIED SEALING TAPE

Key Benefits Summary

- Overpaintable
- Waterproofing sealing repair tape
- Easily repaired

PRODUCT INFORMATION

DESCRIPTION

A self-adhesive cold applied sealing tape recommended for all substrate sealing repairs on asphalt, bituminous sheets, glass, metal, plastics, timber, mortar, concrete, bricks, rooftiles, stone. Seal guttering, downpipes, roof sheets or flashings. Seal cracked brickwork, concrete, tiles or glass. Seal carport or verandah roof to main wall. Seal window frames.

PACKAGING

Available in rolls of;

- 50mm x 3m
- 75mm x 3m
- 50mm x 10m
- 75mm x 10m
- 100m x 10m
- 150mm x 10m

TECHNICAL INFORMATION

Composite laminate of;

- An aluminium foil carrier,
- A self adhesive rubber modified compound and,
- A silicone coated release interleave.
(Removed during application.)

Thickness - 1.5mm

Temperature Resistance -40°C - +100°C

Weather Resistance - Not affected by water or heat

Breaking Strength - 127N/25.4 mm on steel

Colour - Aluminium

STORAGE LIFE

Store upright in a cool, dry place.

DISPOSAL

Collect and dispose of according to local regulations.

USAGE GUIDELINES

APPLICATION

- Apply at temperatures above 5°C.
- Check the substrates are clean, dry and free of loose particles.

- Cut the strips to the required length, pull off the release paper.
- and apply strip to the surface to be waterproofed by pressing the strip by hand or with a metal roller to the substrate.
- Overlap strips by 3cm.

When applying Flash Patch to timber, mortar, concrete, bricks, rooftiles and stone, it is recommended to prime the surface with one coat of Pabco Bitumen Paint to stabilise the substrate.

TECHNICAL SERVICE

TREMCO has a team of qualified Technical Sales Representatives who provide assistance in the selection and specifications of products. For more detailed information or service and advice call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

GUARANTEE/WARRANTY

We warrant our products to be free of defects and manufactured to meet published physical properties when tested according to applicable specifications and TREMCO standards.

Under this warranty we will provide at no charge, product to replace any product proven to be defective when applied in accordance with our written instructions and in applications recommended by TREMCO as being suitable for this product.

All claims concerning product defects must be made within 12 months of shipment. Absence of such claims in writing during this period will contribute a waiver of all claims with respect to such product. This warranty is in lieu of any and all other warranties expressed or implied.