

# Gun Grade Hydroseal

## BITUMEN BASED, FIBRE REINFORCED ROOF REPAIR SEALANT

### Key Benefits Summary

- Easy to apply
- Remains flexible at lower temperatures
- Will not sag or run
- Adheres to wet or dry surfaces
- Asbestos Free

### PRODUCT INFORMATION

#### DESCRIPTION

Gun Grade Hydroseal is a specially formulated bitumen based material reinforced with non asbestos fibres for additional strength and durability. The product is designed to provide a tough, long lasting waterproof seal, ideal for repairing damaged or worn out roofs, shingles and flashings.

- Seals holes up to 7mm.
- One coat application on most surfaces - easily applied.
- Minimal surface preparation required.
- Remains flexible at lower temperatures - will not peel or crack.
- Will not run or sag - may be used on vertical or horizontal surfaces.
- Adheres to wet or dry surfaces - good for emergency repairs.
- Asbestos free formulation.

#### BASIC USES

Gun Grade Hydroseal is perfect for the repair of worn-out roofs, shingles, flashings, guttering, downpipes and around pipe penetrations.

#### PACKAGING

300ml Cartridge

#### COLOUR

Black

#### USAGE GUIDELINES

#### APPLICATION

Surface must be clean, dry, free from dirt, wax, oily residue and any loose paint or rust. The material may be applied to a wet surface and during rain in an emergency situation. Any cracks up to 7mm deep should be filled with Gun Grade Hydroseal and covered immediately with a 3mm top coat (Brushable Hydroseal/Heavy Grade Hydroseal). Deeper cracks should be filled and allowed to set for one hour to prevent shrinking or cracking of top coat. To repair very deep cracks or holes in gutters, embed fibreglass or wire screen and cover with 3mm topcoat. Use mineral spirits for clean up.

### TECHNICAL INFORMATION

#### TYPICAL PERFORMANCE CHARACTERISTICS

PROPERTIES	TEST METHOD	TYPICAL VALUE
Vehicle		Bituminous
Solvent		Mineral Spirits
Flash Point		43°C
Viscosity	Brookfield #6	13,200 poise
Tack Free Time		72 hours
Application Temperature (ambient)		-7°C minimum
Weathering		Very Good

#### AVAILABILITY

Gun Grade Hydroseal is available through your nearest Tremco stockist.

#### HEALTH AND SAFETY PRECAUTIONS

Material Safety Data Sheet must be read and understood before use.

#### TECHNICAL SERVICE

TREMCO has a team of qualified Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information or service and advice call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

#### GUARANTEE/WARRANTY

We warrant our products to be free of defects and manufactured to meet published physical properties when tested according to applicable specifications and TREMCO standards.

Under this warranty we will provide at no charge, product to replace any product proven to be defective when applied in accordance with our written instructions and in applications recommended by TREMCO as being suitable for this product.

All claims concerning product defects must be made within 12 months of shipment. Absence of such claims in writing during this period will contribute a waiver of all claims with respect to such product. This warranty is in lieu of any and all other warranties expressed or implied.

TREMCO PTY LTD ABN 25 000 024 064  
Unit 1, 2 Park Rd, Rydalmere NSW 2116, Australia  
Tel: (02) 9638 2755 Fax: (02) 9638 2955  
tremco@tremco.com.au

Gun Grade Hydroseal