

Paramastic™

EXPANDABLE MASTIC FOR USE WITH PARASEAL

Key Benefits Summary

- One Part
- Easy Application
- Contains Bentonite

PRODUCT INFORMATION

DESCRIPTION

Paramastic is an expandable mastic and caulk for use with Paraseal waterproofing membrane.

BASIC USES

To protect against water leakage in the areas of: penetration, honeycombs, unfilled ties or spalled concrete. Paramastic is an important part of the Paraseal waterproofing system - substitutions are not allowed.

MATERIALS

A thick paste containing expandable bentonite designed to be applied over dry, damp, frozen or uncured concrete. Product reacts to and stiffens in the presence of water to form an impervious membrane.

PACKAGING

19 litre pails
7.57 litre pails

LIMITATIONS

Do not apply in standing water or over ice or snow.

USAGE GUIDELINES

INSTALLATIONS

Preparatory Work:

Remove dust and oozeings. Trowel over honeycombs deeper than 6.3mm. Fill all tie holes and spalled areas prior to the installation of Paraseal.

General:

Always cover Paramastic with a protective layer of Paraseal membrane. All vertical inside corners receive a cove detail of Paramastic.

Penetrations:

Place 25mm cove around all penetrations and extend 38mm beyond.

Lagging:

Apply Paramastic around all tie-backs and penetrations. Protect with 100 micron polyethylene or a protective layer of Paraseal LG.

Storage:

Paramastic will not react to air, however, care must be taken to prevent water contamination in container.

TECHNICAL INFORMATION

Physical Properties

Physical Properties	Value
Colour	Grey/Black
Resistance to Micro-Organisms (bacteria, fungi, mould, yeast)	Unaffected
Resistance to water migration	100%
Co-efficient of permeability	1.0 x 10 ⁻⁹
Freeze/Thaw cycle (-15°F)	Unaffected
Rain Resistance	48 Hours
Fiber or Filler	0%
Flash Point	Approx 174°C
Specific Gravity	1.2
Weight	Approx 1.2Kg/Ltr

HEALTH AND SAFETY PRECAUTIONS

Material Safety Data Sheet must be read and understood before use.

TECHNICAL SERVICE

TREMCO has a team of qualified Technical Sales Representatives who provide assistance in the selection and specifications of products. For more detailed information or service and advice call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

GUARANTEE/WARRANTY

We warrant our products to be free of defects and manufactured to meet published physical properties when tested according to applicable specifications and TREMCO standards.

Under this warranty we will provide at no charge, product to replace any product proven to be defective when applied in accordance with our written instructions and in applications recommended by TREMCO as being suitable for this product.

All claims concerning product defects must be made within 12 months of shipment. Absence of such claims in writing during this period will contribute a waiver of all claims with respect to such product. This warranty is in lieu of any and all other warranties expressed or implied.