

MATERIAL SAFETY DATA SHEET

EZY SEAL General Purpose Silicone Sealant (Roofs and Gutters)

Issue: 1

Issue Date: 1st July 2000

Re-Issued 19th September, 2005

Page 1 of Total 3

STATEMENT OF HAZARDOUS NATURE

Not hazardous according to criteria of Worksafe Australia

COMPANY DETAILS

Company: Tremco Pty Limited
Address: Unit 1, 2 Park Rd, RYDALMERE NSW 2116
Telephone no: 02 96382755
Facsimile no: 02 96382955
Emergency Telephone no: 1800224512 (business hours only)

IDENTIFICATION

Product Name: General Purpose Silicone Sealant

Other Names:

UN Number: Not Applicable

Dangerous Goods Class and Subsidiary Risk: Not Applicable

Hazchem Code: Not Applicable

Poisons Schedule Number: Not Scheduled

Use: A general purpose neutral oxime sealant.

Physical Description/Properties

Appearance: Clear paste with slight odour

Boiling Point: Not known

Melting Point: No data available

Specific Gravity: 1.03

Flashpoint: 63^oC

Flammability Limits: Not Applicable

Other Properties:

Solubility in Water: Immiscible

Ingredients:

Ingredients are non-hazardous according to Worksafe Australia criteria and primarily consist of silicone polymers.

HEALTH HAZARD INFORMATION**Health Effects:****Acute:**

Swallowed: May be harmful if swallowed.
Eye: A possible mild irritant whilst in the uncured state
Skin: A possible mild irritant, particularly on prolonged skin contact when uncured.
Inhaled: Repeated or prolonged exposure to vapour may cause mild irritation to mucous membrane and respiratory tract.

Chronic: No data available.

First Aid:

Swallowed: Induce vomiting. Seek medical attention if symptoms evident.
Eye: Flood with water for at least 15 minutes, holding eyelids open. Seek medical attention if irritation persists.
Skin: Wash thoroughly with soap and water.
Inhaled: Remove patient to fresh air.
First Aid Facilities: Eye wash and general wash facilities should be easily accessible to workplace.
Advice to Doctor: Not known

PRECAUTIONS FOR USE

Exposure Standards: No data available for product. Data supplied is for constituents within the product.
Formaldehyde 1ppm/1.2mg/m³ TWA
2ppm/2.5mg/m³ STEL

Engineering Controls: Eyewash station

Personal Protection: Wearing of gloves and safety goggles is recommended to avoid contact with skin or eyes, especially if applying product overhead to avoid eye-contact if split. Wear clean, long sleeved, body-covering clothing. Remove contact lenses before using. Do not handle lenses unless sealant has been removed from fingertips.

Flammability: Not flammable.

SAFE HANDLING INFORMATION

Storage and Transport: This product is not classified as a dangerous good under the provisions of the “Australian Code for the Transport of Dangerous Goods by Road and Rail”. Check containers are clearly labelled. Keep containers sealed when not in use. Keep away from heat, store in a cool place. Product releases acetic acid during application.

Spills and Disposal: Product does not flow easily and spills may therefore be collected easily for disposal. Wash residual product away with plenty of water. Do not allow product to enter drains.

Fire/Explosion Hazard: Product is non-flammable and does not pose any fire or explosion hazard.

OTHER INFORMATION

Contact Point: The Managing Director
Telephone no: 1800224512 (business hours)

The information provided by TREMCO in relation to TREMCO's goods or their use is given in good faith, which has been compiled from various sources and is believed by TREMCO to be appropriate and reliable. The actual use and application of the goods will vary with application conditions which are beyond our control. TREMCO makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information.