

MATERIAL SAFETY DATA SHEET

Ezy Bond - Construction Adhesive

Issue Date: 4th May 2000

Re-issue Date 5th December, 2007

Page 1 of Total 3

STATEMENT OF HAZARDOUS NATURE

Classified as hazardous according to criteria of Worksafe Australia

COMPANY DETAILS

Company: Tremco Pty Limited
Address: Unit 1, 2 Park Rd, RYDALMERE NSW 2116
Telephone no: 02 96382755
Facsimile no: 02 96382955
Emergency Telephone no: 1800224512 (business hours only)

IDENTIFICATION

Product Name: Ezy Bond - Construction Adhesive
Other Names: None used
UN Number: 1133
Dangerous Goods Class/Subsidiary Risk: Class 3
Proper Shipping Name: Adhesive containing petroleum spirit
Packing Group: III
Poisons Schedule Number: Not scheduled

Use: Used as a construction adhesive in the building industry to bond various substrates.

Physical Description/Properties

Appearance: Greyish brown semi-solid paste
Boiling Point: 62 °C
Melting Point: No data available
Specific Gravity: Approx.1.08
Flashpoint: <-30°C
Flammability Limits: 1-7.5%
Solubility in Water: Insoluble
Other Properties: Not Applicable

Ingredients

Chemical Name:	CAS Number:	Proportion:
A Petroleum spirit	64742-49-0	30-60%
B Aliphatic/aromatic hydrocarbon Resins	Not available	10-30%
C Fillers	Not available	30-60%
D Synthetic rubbers	66070-58-4	10-30%
E Other non-hazardous ingredients		

HEALTH HAZARD INFORMATION

Health Effects:

Acute:

Swallowed: An unlikely route of entry. If ingested frothing may occur due to substance A which may lead to vomiting and aspiration into the lungs.

Eye: May cause a mild irritation.

Skin: No effects are expected.

Inhaled: Irritating to respiratory system due to Substance A. May cause dizziness, nausea. Large doses can cause unconsciousness.

Chronic: Prolonged or repeated contact will dry and defat the skin, eventually causing irritation and dermatitis.

First Aid:

Swallowed: If swallowed, rinse mouth thoroughly with water. Give plenty of water to drink. Do NOT induce vomiting. Seek medical attention immediately.

Eye: If in eye, irrigate immediately with copious amounts of water for 15 minutes with eyelids held open. Seek medical attention.

Skin: Wash contact area with soap and water. Remove contaminated clothing. Launder before re-use. If irritation persists seek medical attention.

Inhaled: Remove patient to fresh air. Seek medical attention if required.

First Aid Facilities: Eyewash facility and general wash area should be accessible.

Advice to Doctor: Treat symptomatically.

PRECAUTIONS FOR USE

Exposure Standards: No data available for this product. Exposure limits for the solvents are Hexane Worksafe standard TWA TLV 100 ppm, STEL 150 ppm

Engineering Controls: General dilution ventilation should be sufficient for application in external areas.

PRECAUTIONS FOR USE

Personal Protection: Avoid skin and eye contact. Wear chemically resistant gloves conforming to AS 2161 and safety glasses when using. Long sleeved clothing or disposable overalls should be used to avoid skin contact. If insufficient ventilation is available or in the event of a spill a canister type half face respirator with a cartridge suitable for organic vapours should be used.

Flammability: Flammable, Exclude all sources of ignition and static generators from the work area. No smoking.

SAFE HANDLING INFORMATION

Storage and Transport: Store in a cool, dry place do not store over 50 C. Keep away from all sources of ignition. Keep containers tightly sealed when not in use.

UN Number: 1133
Dangerous Goods Class/Subsidiary Risk: Class 3
Proper Shipping Name: Adhesive containing petroleum spirit
Packing Group: III

Under the Dangerous Goods Code Six this product is not required to be labelled according to dangerous goods regulations.

Spills and Disposal: Remove all ignition sources from the area and keep people away. Spill should be prevented from entering waterways.. Avoid breathing the vapour and ventilate enclosed spaces. Breathing apparatus should be worn if any risk of overexposure. Recover the spilt material using absorbent material e.g sand, earth or sawdust. Dispose of in accordance to Local, State and Federal regulations as a solvent containing waste material.

Fire/Explosion Hazard: Wear self-contained breathing apparatus. Carbon Monoxide and Carbon Dioxide are combustion by-products.
Extinguishing media - alcohol type Foam, Carbon Dioxide or dry chemical powder.. Vapours are heavier than air and may collect in depressions. Vapours may travel to the source of ignition.

OTHER INFORMATION

Contact Point: The OHS&E Officer
Tremco Pty Limited
Unit 1, 2 Park Road Rydalmere NSW 2116
Telephone no: 1800 224 512 (business hours)

The information provided by TREMCO in relation to TREMCO's goods or their use is given in good faith, which has been compiled from various sources and is believed by TREMCO to be appropriate and reliable. The actual use and application of the goods will vary with application conditions which are beyond our control. TREMCO makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information.

