



08/09

PRODUCT  
DATA  
SHEET

2 Pages

# EZY BOND—Construction Adhesive

For bonding floor boards, wall panels and most common building materials

## PRODUCT DESCRIPTION

EZY BOND is a fast setting, high strength, synthetic rubber based adhesive. Use as an alternative to nails and screws, as a timber construction adhesive and also as an adhesive for most other common building materials. Meets Australian Standard

## KEY BENEFITS SUMMARY

- High bond strength
- Fast grab
- Low solvent (polystyrene safe)
- Flexible
- Wood colour—paintable, Interior/Exterior Multipurpose,
- Waterproof

## USAGE/PURPOSE

- Bonding sheet flooring to joists
- Tongue and groove flooring
- Fixing wallboards/panels to studs or solid walls
- Installing skirting boards and polystyrene foam

## PACK SIZE

300ml Cartridges (20 per carton)

## COLOUR

Beige

## PRODUCT CODE

235215

## TECHNICAL INFORMATION

Appearance:	Greyish brown semi-solid paste
Boiling Point:	62°C
Specific Gravity:	Approx. 1.08
Flashpoint:	< - 30°C
Solubility in Water:	Insoluble

NOTE: Typical properties should not be used as specifications

## USAGE GUIDELINES

### SURFACE PREPARATION

- Surfaces must be clean, dry and free from dust, grease, old sealant or flaking paint

### METHOD OF APPLICATION

- Cut tip at 45° angle to the width of the gap to be filled. Hold gun at 45° angle push sealant ahead of nozzle so it wets both sides of the joint
- For joints deeper than 12mm, apply a backer rod
- Tool sealant using a knife dipped in soapy water within 8—10 minutes of application
- Product skins in 8—10 minutes, and fully cures in 5—6 days

### COVERAGE

Approximately 12m for a 5mm x 5mm bead

### CLEAN UP

Wipe clean with a cloth before curing. Cured sealant requires mechanical removal

### STORAGE

Store in a cool dry place below 30°C



# EZY BOND—Construction Adhesive

## SHELF LIFE

12 months when stored as recommended in original unopened containers

## HEALTH AND SAFETY PRECAUTIONS

Material Safety Data Sheet (MSDS) must be read and understood prior to use

## TECHNICAL SERVICE

TREMCO has a team of qualified Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information or service and advice call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

## GUARANTEE/WARRANTY

TREMCO products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with TREMCO written instructions and (b) in any application recommended by TREMCO, but which is proved to be defective, will be replaced free of charge.

Any information provided by TREMCO in this document in relation to TREMCO's goods or their use is given in good faith and is believed by TREMCO to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application may vary with application conditions which are beyond our control. TREMCO makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.