



07/11

PRODUCT  
DATA  
SHEET

2 Pages

# EZY FILL—Acrylic Gap Sealant

For filling of cracks and gaps around the home

## PRODUCT DESCRIPTION

EZY FILL is a non toxic, non hazardous, durable acrylic gap sealant, for use where movement would cause rigid fillers to crack and fall out.

## KEY BENEFITS SUMMARY

- Paintable
- Flexible
- Water clean-up
- Interior/Exterior
- Smooth finish
- Fast drying
- Mould & Mildew resistant

## USAGE/PURPOSE

- Plasterboard
- Brick work
- Timber
- Concrete
- Dry wall
- Particle board

## PACK SIZE

300ml Cartridges (20 per carton)

## COLOUR

White

## PRODUCT CODE

235216

## TECHNICAL INFORMATION

Appearance	Thick white paste
Flashpoint	Not Flammable
Solubility in Water:	Miscible
Movement capabilities	+/- 12%

NOTE: Typical properties should not be used as specifications

## USAGE GUIDELINES

### SURFACE PREPARATION

- Surfaces must be clean, dry and free from dust, grease, old sealant or flaking paint
- Should masking be required to prevent contamination of adjacent surfaces, it is recommended that the masking tape be removed immediately after tooling

### METHOD OF APPLICATION

- Cut nozzle at 45° angle to the width off gap to be filled. Screw nozzle onto cartridge and place cartridge in cartridge gun
- For joints deeper than 12mm use a backer rod
- Hold gun at 45° angle and squeeze trigger pushing sealant ahead of nozzle so it completely fills the gap, wetting both sides
- Immediately after application tool sealant smooth with wet knife
- Product skins in 30 minutes and can be painted with an acrylic paint. If using an oil based paint allow 24 hrs drying prior to painting

### LIMITATIONS

- Painting over product will improve the exterior durability
- Do not use outside if the rain imminent
- Do not use on tongue and groove boards or 4" weatherboard overlaps
- Not suitable for constant water immersion



# EZY FILL—Acrylic Gap Sealant

## COVERAGE

Approximately 12m for a 5mm x 5mm bead

## CLEAN UP

Wipe clean with a cloth before curing. Cured sealant requires mechanical removal

## STORAGE

Store in a cool dry place below 30°C

## SHELF LIFE

12 months when stored as recommended in original unopened containers

## HEALTH AND SAFETY PRECAUTIONS

Material Safety Data Sheet (MSDS) must be read and understood prior to use

## TECHNICAL SERVICE

TREMCO has a team of qualified Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information or service and advice call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

## GUARANTEE/WARRANTY

TREMCO products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with TREMCO written instructions and (b) in any application recommended by TREMCO, but which is proved to be defective, will be replaced free of charge.

Any information provided by TREMCO in this document in relation to TREMCO's goods or their use is given in good faith and is believed by TREMCO to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application may vary with application conditions which are beyond our control. TREMCO makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.