

Anti-Root Additive

Anti-root Additive for TREMproof 250GC, TREMproof 60 and TREMproof P85

PRODUCT DESCRIPTION

Anti-root Additive for TREMproof 250GC, TREMproof 60 and TREMproof P85.

USAGE/PURPOSE

While Tremco Anti-root Additive will provide resistance to most root systems, it is always recommended that plants with non invasive root systems be used in planter boxes and general landscape projects.

FEATURES & BENEFITS

- Protects construction materials from undesirable root penetration without damaging plants.
- Provides long-term protection.
- Remains effective also under harsh weathering conditions.
- Is heat-resistant and has a very low vapour pressure. The effectiveness of the active ingredient is virtually unaffected by the high temperatures required to process bitumen and welding roofing felts.
- Has good compatibility with most bituminous construction materials.

PACKAGING

100ml bottle

COLOUR

Amber

SHELF LIFE / STORAGE

Provided the product is correctly stored and kept in the original sealed package, its shelf life is at least 2 years.

METHOD OF APPLICATION

Add full contents of bottle into pail and mix thoroughly for 5 minutes with a electric mechanical mixer. Apply TREMproof 250GC, TREMproof 60 and TREMproof P85 in accordance with Tremco's Data Sheets.

CLEAN UP

- Excess sealant and smears adjacent to the joint interface can be carefully removed with Tremco Xylol before the sealant cures.
- Any utensils used for tooling can also be cleaned with Tremco Xylol, mineral spirits or white spirits.

HEALTH & SAFETY PRECAUTIONS

Anti-root Additive is a viscous liquid. Contact of the product with the skin and the inhalation of vapours should be avoided. The precautions generally recommended for handling chemicals should be observed, eg. wearing of protective clothing, protective gloves and safety goggles. If the product comes into contact with the skin, the affected area should be washed immediately with large amounts of soap and plenty of water; splashes in the eye should be rinsed out immediately with plenty of water. If irritation persists, medical attention should be obtained. Contaminated clothing should be changed at once. The Safety Data Sheet (SDS) must be read and understood prior to use.



TECHNICAL SERVICE

Tremco CPG Australia Pty Ltd has a team of Representatives who provide assistance in the selection and specification of products. For more detailed information or service and advice, call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

GUARANTEE/WARRANTY

Tremco CPG Australia Pty Ltd products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG Australia written instructions and (b) in any application recommended by Tremco CPG Australia, but which is proved to be defective, will be replaced free of charge.

Any information provided by Tremco CPG Australia in this document in relation to Tremco CPG Australia's goods or their use is given in good faith and is believed by Tremco CPG Australia to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. Tremco CPG Australia makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

CONTACT OUR TEAM

Tremco CPG Australia Pty Ltd
 ABN: 25 000 024 064
 Unit 12, 4 Southridge Street
 Eastern Creek, NSW 2766

P: (02) 9638 2755
 F: (02) 9638 2955
 E: tremco@tremco.com.au

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUES
Density (20°C)		Approx. 1.21 g/cm ³
Solidification Point		Approx. -12°C
Boiling Point	DIN 53171	Above 300°C at 1013 hPa
Flash Point	DIN 22719	Approx. 242°C
Ignition Temperature	DIN 51794	Approx. 425°C
Solubility (20°C)		Slight soluble in water, soluble in bitumen, tar pitches and organic solvents such as toluene and xylene