

Evencure EP Ezispray

Fine Particle, High Solids, Modified Bitumen Emulsion

PRODUCT DESCRIPTION

Evencure EP Ezispray is a fine particle, high solids, modified CRS 170 bitumen emulsion. Due to its unique formulation Evencure EP Ezispray can be applied through standard spray equipment including gear pumps and once dried is a trafficable coating.

USAGE/PURPOSE

Evencure EP Ezispray is suitable for the following applications:

- Primer sealing unbound or bound gravel surfaces
- Primer for salt affected surfaces
- Tack coat for overlay application
- Waterproofing of the "select" base to protect against water ingress
- Priming of concrete substrates requiring asphalt
- Resealing with aggregate

FEATURES & BENEFITS

Due to the unique formulation of Evencure EP Ezispray, this product, unlike typical emulsions, does not require heating nor does it require "special" pumps.

- Evencure EP Ezispray is highly stable in storage, with minimal settlement over a 6 month period.
- Can be sprayed at any temperature without heating
- Penetrates deeper into the substrate than traditional bitumen emulsions. (SA DOT testing)
- Minimal "pick up" when cured compared to traditional items
- Totally waterbased with no solvent odour
- Complies to State requirement for CRS-170 Bitumen Emulsion types
- Creates a waterproof layer to protect the substrate

PACKAGING

- 1000L Tote

COLOUR

- Black



SHELF LIFE

6 months when stored as recommended in original unopened packaging.

USAGE

Due to the large amount of different applications suitable for this product it is advisable to adhere to "typical application rates" or as required as set out by ARRB, Vicroads, RMS or a specifying engineer. However, typical application rates by spray or roller are as follows:

Product	Application Area	Coverage Rate
Evencure EP Ezispray	Primer Seals	0.75 - 1.5 L/m ²
	Tack Coat	0.15 - .50 L/m ²
	Surface Enrichment	0.5 0 1.2 L/m ²
	Concrete Pumping	.25 - .5 Lt/m ²

HEALTH & SAFETY PRECAUTIONS

The Safety Data Sheet (SDS) must be read and understood prior to use.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	RESULT	
Appearance	Black free flowing liquid	
Viscosity	.1 Pascal seconds	
Solids	50% or greater	
Solubility in Water	Soluble	
Flash Point	Not applicable	
Solvents	Not applicable	
Dry Time	Tack Free	1 - 3 Hours
	Hard Dry	4 - 8 Hours
	Trafficable	24 Hours
Application Temperature	10°C - 35°C	

*Dry times will vary depending on ambient temperature and relative humidity

TECHNICAL SERVICE

Tremco CPG Australia Pty Ltd has a team of Representatives who provide assistance in the selection and specification of products. For more detailed information or service and advice, call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

GUARANTEE/WARRANTY

Tremco CPG Australia Pty Ltd products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG Australia written instructions and (b) in any application recommended by Tremco CPG Australia, but which is proved to be defective, will be replaced free of charge.

Any information provided by Tremco CPG Australia in this document in relation to Tremco CPG Australia's goods or their use is given in good faith and is believed by Tremco CPG Australia to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. Tremco CPG Australia makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

CONTACT OUR TEAM

Tremco CPG Australia Pty Ltd

ABN: 25 000 024 064

Unit 12, 4 Southridge Street

Eastern Creek, NSW 2766

P: (02) 9638 2755

F: (02) 9638 2955

E: tremco@tremco.com.au