

## PRODUCT DESCRIPTION

Evenrange Ecolease is a water based concrete release agent designed to work in a variety of applications. It is particularly well suited to releasing concrete from timber or metal framework.

## USAGE/PURPOSE

Releasing concrete from timber or metal framework.

## FEATURES & BENEFITS

- Environmentally friendly
- 100% biodegradable
- Bio-based
- Low aqua-toxicity
- User friendly
- Free of solvents
- Non-hazardous/Non flammable
- Non-staining
- Dries clear

## PACKAGING

- 20L Pail
- 200L Drum
- 1000L Tote

## COLOUR

Milky homogenous liquid at 25°C, dries clear.

## SHELF LIFE

12 months when stored as recommended in original unopened packaging.

## STORAGE

- Store in a cool place and out of direct sunlight.
- Store in original packaging.

## LIMITATIONS

Treated formwork should not be left standing for extended periods. It is important that such surfaces are kept cleaned prior to and after application. Unsealed timber will require 2-3 applications before use. Tools and other items can be cleaned with water.

## USAGE

Product	Application Area	Coverage Rate
Evenrange Ecolease	Steel	Approx 30m <sup>2</sup> /L
Evenrange Ecolease	Timber	Approx 19m <sup>2</sup> /L

## METHOD OF APPLICATION

Apply a thin film of Evenrange Ecolease to a clean, dry surface. This can be done using a high pressure spray, brush or roller at a rate of approx. 30m<sup>2</sup>/L for steel and approx. 19m<sup>2</sup>/L for timber. Coverage rate, temperature, humidity, wind and absorption will effect drying time. Allow sufficient time for water component to evaporate before removing excess material using a brush or cloth to avoid puddling product. Product is dry when milky appearance has disappeared.



## HEALTH & SAFETY PRECAUTIONS

The Safety Data Sheet (SDS) must be read and understood prior to use.

## TECHNICAL SERVICE

Tremco CPG Australia Pty Ltd has a team of Representatives who provide assistance in the selection and specification of products. For more detailed information or service and advice, call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

## GUARANTEE/WARRANTY

Tremco CPG Australia Pty Ltd products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG Australia written instructions and (b) in any application recommended by Tremco CPG Australia, but which is proved to be defective, will be replaced free of charge.

Any information provided by Tremco CPG Australia in this document in relation to Tremco CPG Australia's goods or their use is given in good faith and is believed by Tremco CPG Australia to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. Tremco CPG Australia makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

## CONTACT OUR TEAM

Tremco CPG Australia Pty Ltd  
 ABN: 25 000 024 064  
 Unit 12, 4 Southridge Street  
 Eastern Creek, NSW 2766

P: (02) 9638 2755

F: (02) 9638 2955

E: tremco@tremco.com.au