

PRODUCT DESCRIPTION

Evenrange Stripcure WB is a blend of powerful surfactants in a pre-blended mild solvent. It is ideal for removing curing compounds from concrete prior to the placement of aftertreaters.

Stripcure is environmentally safe and minimises exposure of toxic chemicals in the workplace.

USAGE/PURPOSE

- Stripcure WB is suitable for removing solvent based, single pack coatings
- Stripcure WB will remove hydrocarbon resins, solvent based acrylics and chlorinated rubber coatings in a single application

FEATURES & BENEFITS

- Removes most single pack coatings
- Contains no harsh solvents
- One coat application
- Washes off with water
- Low solvent odour
- 99% Biodegradable
- Stripcure WB contains no Xylene, MEK, Acetone or any other harsh solvents
- Stripcure WB can be used in confined spaces with the correct breathing/mask requirements and ventilation

PACKAGING

- 20lt drum
- 205lt drum

COLOUR

Red liquid

METHOD OF APPLICATION

- Apply Stripcure WB to the desired coating to be removed at a rate of 4-5m² per litre
- Allow Stripcure WB to penetrate the surface for a least 15 minutes. (Maximum 4 hours)
- After the required period pressure wash (minimum 1100psi) the Stripcure and the emulsified coating off the concrete surface

NOTE: It is important that the surface treated is thoroughly flushed with water to remove all residue

SHELF LIFE

12 Months Maximum

HEALTH & SAFETY PRECAUTIONS

The Safety Data Sheet (SDS) must be read and understood prior to use.



TECHNICAL SERVICE

Tremco CPG Australia Pty Ltd has a team of Representatives who provide assistance in the selection and specification of products. For more detailed information or service and advice, call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

GUARANTEE/WARRANTY

Tremco CPG Australia Pty Ltd products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG Australia written instructions and (b) in any application recommended by Tremco CPG Australia, but which is proved to be defective, will be replaced free of charge.

Any information provided by Tremco CPG Australia in this document in relation to Tremco CPG Australia's goods or their use is given in good faith and is believed by Tremco CPG Australia to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. Tremco CPG Australia makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

CONTACT OUR TEAM

Tremco CPG Australia Pty Ltd
 ABN: 25 000 024 064
 Unit 12, 4 Southridge Street
 Eastern Creek, NSW 2766
 P: (02) 9638 2755
 F: (02) 9638 2955
 E: tremco@tremco.com.au

TYPICAL PROPERTIES

TYPICAL PROPERTIES		
Coverage		4-5m ² per litre
Viscosity		0.03 pas sec.
Solids		Not Applicable
Solubility with Water		Soluble
Flash Point		87°C
Solvents		Not Applicable
Dry Time	Tack Free	Not Applicable
	Hard Dry	Not Applicable
Application Temp		5°C - 40°C