

PRODUCT DESCRIPTION

A non-woven, staple, needle-punched, geotextile fabric specifically designed as a high flow rate, soil filtration medium to protect planters from soil erosion while providing sufficient water flow to the Tremco drainage solution.

USAGE/PURPOSE

Tremco Geofabric Drainage Fabric is designed to be used in conjunction with Tremco's waterproofing membrane and drainage solutions for planter applications as a soil filtration barrier.

PACKAGING

2m (W) x 50m (L)

COLOUR

White

SHELF LIFE

Unlimited.

STORAGE

Store in a dry cool place in original unopened packaging.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUES
Flow Rate	AS 3706.9	230 L/m ² /second

TECHNICAL SERVICE

TREMCO has a team of Representatives who provide assistance in the selection and specification of products. For more detailed information or service and advice, call Customer Service on (02) 9638 2755.



GUARANTEE/WARRANTY

TREMCO products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with TREMCO written instructions and (b) in any application recommended by TREMCO, but which is proved to be defective, will be replaced free of charge.

Any information provided by TREMCO in this document in relation to TREMCO's goods or their use is given in good faith and is believed by TREMCO to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. TREMCO makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.