

PRODUCT DESCRIPTION

Paraseal Paramastic is a sodium bentonite filled, bitumen based mastic for use with Paraseal waterproofing membranes.

USAGE/PURPOSE

Paraseal Paramastic is used to detail around penetrations, tie backs, and other complex construction to provide a well sealed termination detail of the Paraseal system.

It is also used to form a fillet/cove at all vertical corner transitions and may be used in lieu of Paragranular at floor/wall transitions and penetrations through horizontal surfaces, and to fill voids around substrate irregularities.

PACKAGING

18.9L Pail

COLOUR

Black

SHELF LIFE

12 months when stored as recommended in original unopened packaging.

STORAGE

Store in a dry cool place in an upright position in original unopened packaging.

HEALTH & SAFETY PRECAUTIONS

The Safety Data Sheet (SDS) must be read and understood prior to use.



TECHNICAL SERVICE

TREMCO has a team of Representatives who provide assistance in the selection and specification of products. For more detailed information or service and advice, call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

GUARANTEE/WARRANTY

TREMCO products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with TREMCO written instructions and (b) in any application recommended by TREMCO, but which is proved to be defective, will be replaced free of charge.

Any information provided by TREMCO in this document in relation to TREMCO's goods or their use is given in good faith and is believed by TREMCO to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. TREMCO makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.