

PRODUCT DESCRIPTION

Adjustable paving support for pedestrian accessible roofs. Polypad 2.0 with integrated damper and 1 extension collar.

USAGE/PURPOSE

- Each Polypad has a circular base plate, which has bevelled edges to ensure that no mechanical damage is caused to underlying waterproofing membranes by the Polypad support.
- Spacer lugs allow for a variety of quickly adjustable heights, with a minimum of 30mm to a maximum height of 45mm.

FEATURES & BENEFITS

- Polypad provide rapid drainage of surface water through uniform open joints in the paver surface.
- Eliminates any concern of efflorescence as there is no screed or tiling grout present in the paver system.
- Eliminates the risk of debonding pavers as a result of improper installation and/or tile movement.
- Promotes maximum design flexibility as the pavers are easy to remove and changed for future facility use or stylistic changes in the future.
- Provides convenient area under the paver to run utilities to garden beds or podium/roof area lighting.

COMPOSITION

High resistance Polypropylene

ADJUSTEMENT WITH DEDICATED TOOL

The adjustment is always downwards and never upwards in order to not break the internal damper

Procedure:

- Polypad 2.0 is placed in its higher position.
- Concrete pavement is installed.
- Polypad 2.0 position is adjusted downwards using the dedicated tool.



HEALTH & SAFETY PRECAUTIONS

The Safety Data Sheet (SDS) must be read and understood prior to use.

TECHNICAL SERVICE

TREMCO has a team of Representatives who provide assistance in the selection and specification of products. For more detailed information or service and advice, call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

GUARANTEE/WARRANTY

TREMCO products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with TREMCO written instructions and (b) in any application recommended by TREMCO, but which is proved to be defective, will be replaced free of charge.

Any information provided by TREMCO in this document in relation to TREMCO's goods or their use is given in good faith and is believed by TREMCO to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. TREMCO makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

Physical Properties	
Base Surface	300 cm ²
Mechanical Resistance at -20°C, 23°C and 50°C	15 kN (load applied along plot axis over 100% plot surface)
	7.5 kN (load applied over 25% plot surface)
Dimension Polypad 2.0	40-60mm; 60-100mm; 100-140mm
Dimension Extension Collar (Rehausse)	40mm

CONTACT OUR TEAM

Tremco CPG Australia Pty Ltd
 ABN: 25 000 024 064
 Unit 12, 4 Southridge Street
 Eastern Creek, NSW 2766
 P: (02) 9638 2755
 F: (02) 9638 2955
 E: tremco@tremco.com.au

