

TREMproof FBM Plus Cover Tape

Single-Side Pressure Sensitive Adhesive Sealed Tape

PRODUCT DESCRIPTION

TREMproof FBM Plus Cover Tape is a specially engineered pressure sensitive tape designed for use with the TREMproof FBM Plus membrane to form a robust waterproofing system. Featuring a multilayered design, the tape combines an aggressive adhesive on the bottom for strong bonding with TREMproof FBM Plus membrane and a weather-resistant top layer with a removable release liner. Its protective white coating allows concrete to be cast directly against it, ensuring flawless integration during construction. Together, these features create a continuous, integral seal that eliminates weak points, safeguards against water ingress and extends the structures lifespan.

USAGE/PURPOSE

TREMproof FBM Cover Tape is used for the sealing of overlapping edges and minor membrane repairs for the TREMproof FBM Plus membrane.

PACKAGING

- ❑ Roll Size: 120mm (W) x 50m (L) x 0.35mm (T)
- ❑ 8 Rolls per box

COLOUR

White

SHELF LIFE

12 months

STORAGE

Store in well-ventilated and dry location. Storage temperature should be below 45°C and kept away from direct sunlight, rain and high temperature. Avoid contact with acids, alkali, oils and organic solvents.

LIMITATIONS

- ❑ Do not apply at temperatures below 5°C. Reduced adhesion may occur at lower temperatures.
- ❑ Substrate must be clean, dry and free from dust, laitance, oil, grease or other contaminants that may affect adhesion.
- ❑ Application to damp, wet or contaminated surfaces may result in reduced bond performance.
- ❑ Adequate pressure must be applied to ensure full contact and adhesion of the tape to the substrate.
- ❑ Product is designed for use as part of the TREMproof FBM Plus system and should be used in accordance with system installation guidelines.

INSTALLATION

1. Use a marking pen to identify the reinforced sealing areas, then remove any loose particles from the sheet surface with a metal brush.
2. Cut the adhesive tape to the appropriate length, shape it into a round or oval form and apply it to the reinforced repair area.
3. Apply pressure to the tape using a hand pressure roller while removing the release liner to ensure reliable bonding.



HEALTH & SAFETY PRECAUTIONS

The Safety Data Sheet (SDS) must be read and understood prior to use.

TECHNICAL SERVICE

Tremco CPG Australia Pty Ltd has a team of Representatives who provide assistance in the selection and specification of products. For more detailed information or service and advice, call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

GUARANTEE/WARRANTY

Tremco CPG Australia Pty Ltd products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG Australia written instructions and (b) in any application recommended by Tremco CPG Australia, but which is proved to be defective, will be replaced free of charge.

Any information provided by Tremco CPG Australia in this document in relation to Tremco CPG Australia's goods or their use is given in good faith and is believed by Tremco CPG Australia to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. Tremco CPG Australia makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

CONTACT OUR TEAM

Tremco CPG Australia Pty Ltd
 ABN: 25 000 024 064
 Unit 12, 4 Southridge Street
 Eastern Creek, NSW 2766

P: (02) 9638 2755
 F: (02) 9638 2955
 E: tremco@tremco.com.au

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	RESULT
Peel Adhesion	ASTM D1876	0.8 N/mm
Bond to Concrete	ASTM D903	1.0 N/mm