

Hazardous, NON-Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: E3 Deep Pour & Xtreme Part C Aggregate

Recommended use: Recommended use: Cement, Portland, chemicalsRestrictions on use: Not known.

Supplier: Tremco CPG Australia Pty Ltd

ABN: 25 000 024 064

Street Address: 12/4 Southridge Street

Eastern Creek NSW 2766

Telephone: 02 9638 2755 **Facsimile:** 02 9638 2955

Emergency Telephone number: 02 9037 2994

2. HAZARDS IDENTIFICATION

This material is hazardous according to the criteria of Safe Work Australia GHS 7.





Signal Word

Danger

Hazard Classifications

Sensitisation - Skin - Category 1 Carcinogenicity - Category 1A

Specific Target Organ Toxicity (Repeated Exposure) - Category 1

Hazard Statements

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

Prevention Precautionary Statements

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust, fume, gas, mist, vapours or spray.

P264 Wash hands, face and all exposed skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/protective clothing including eye/face protection.

Response Precautionary Statements

P101 If medical advice is needed, have product container or label at hand.

P302+P352 IF ON SKIN: Wash with plenty of water and soap. P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse

Product Name: E3 Deep Pour & Xtreme Part C Aggregate

Reference No:

Version: 1.1

Page 1 of 7



Storage Precautionary Statement

P405 Store locked up.

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and

international regulations.

Poison Schedule: Unknown

DANGEROUS GOOD CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

3. COMPOSITION INFORMATION

CHEMICAL ENTITY

CAS NO
PROPORTION

Quartz (SiO2)
Aluminium oxide (Al2O3)
Ingredients determined to be Non-Hazardous

CAS NO
PROPORTION

14808-60-7
1344-28-1
11-<1%
Balance

100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Move to fresh air.

Skin Contact: Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Rinse immediately with plenty of water.

Ingestion: Rinse mouth thoroughly.

PPE for First Aiders: Wear safety shoes, overalls, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Effects may be delayed. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. May cause skin and eye irritation. Symptoms may be delayed.

5. FIRE FIGHTING MEASURES

Hazchem Code: Not applicable.

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

Product Name: E3 Deep Pour & Xtreme Part C Aggregate Reference No: Issued: 2022-09-06 Version: 1.1 Page 2 of 7



Reference No:

Specific hazards: Combustible material.

Fire fighting further advice: On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer. Environmental manager must be informed of all major spillages.

LARGE SPILLS

See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer. Environmental manager must be informed of all major spillages.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable

7. HANDLING AND STORAGE

Handling: See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away. Technical measures (e.g. Local and general ventilation): Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust. Safe handling advice: Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Storage: Store locked up.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Product Name: E3 Deep Pour & Xtreme Part C Aggregate

National occupational exposure limits:

	TWA		STEL		NOTICES
	ppm	mg/m3	ppm	mg/m3	
a-Alumina (Al2O3)					
Aluminium oxide	-	10	-	-	-
Quartz (respirable dust)	-	0.05	-	-	Carc. 1A
Silica Crystalline - Quartz (respirable dust)	-	0.05	-	-	Carc. 1A

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not

Issued: 2022-09-06 Version: 1.1 Page 3 of 7



Reference No:

be exceeded at any time during a normal eight-hour workday.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Avoid generating and inhaling dusts. Use with local exhaust ventilation or while wearing dust mask.

Personal Protection Equipment: SAFETY SHOES, OVERALLS, GLOVES, SAFETY GLASSES, RESPIRATOR.

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

Wear safety shoes, overalls, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

RECOMMENDATIONS FOR CONSUMER USE:

Appropriate EngineeringControlsMechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposurelimits and minimize the risk of inhalation of dust. Individual protection measures, such as personal protective equipment General information: Use personal protective equipment as required. Eye/face protection: Wear goggles/face shield. Skin ProtectionHand Protection: Use suitable protective gloves if risk of skin contact. Other: Wear chemical-resistant gloves, footwear, and protective clothingappropriate for the risk of exposure. Contact health and safety professionalor manufacturer for specific information. Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor. Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing shouldnot be allowed out of the workplace. Avoid contact with skin.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Solid
Colour: Tan
Odour: Odourless

Solubility: Miscible with water. **Solubility in water:** Miscible with water.

Product Name: E3 Deep Pour & Xtreme Part C Aggregate

Density: 2.6

Total VOC (g/Litre): Regulatory VOC (less water and exempt solvent) : 0 g/l /

VOC Method 310: 0.00 %

(Typical values only - consult specification sheet)

Issued: 2022-09-06 Version: 1.1 Page 4 of 7



Reference No:

N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: Material is stable under normal conditions.

Conditions to avoid: Avoid heat or contamination.

Incompatible materials: No data available.

Hazardous decomposition products: Thermal decomposition or combustion may liberate carbon oxides

andother toxic gases or vapors.

Hazardous reactions: No data available.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat andmucus membranes.

Skin contact: May cause an allergic skin reaction. Aluminum oxide in vivo (Rabbit): Not irritant A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Eye contact: Eye contact is possible and should be avoided. Aluminum oxide Rabbit, 24 hrs: Not irritating Exposure to the dust may cause discomfort due to particulate nature. May cause physical irritation to the eyes.

Acute toxicity

Inhalation: This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity estimate (based on ingredients): $LC_{50} > 5.0$ mg/L for dust.

Crystalline Silica (Quartz)/ Silica Sand LC50 (Rat): > 5.0 mg/l Aluminum oxide LC50 (Rat): 7.6 mg/l

Skin contact: This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000 \text{ mg/Kg}$ bw

Ingestion: This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000 \text{ mg/Kg}$ bw

Aluminum oxide LD50 (Rat): > 10,000 mg/kg

Corrosion/Irritancy: Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as not corrosive or irritating to skin.

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as a Category 1 Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as not an aspiration hazard.

Product Name: E3 Deep Pour & Xtreme Part C Aggregate

Specific target organ toxicity (single exposure): This material has been classified as not a specific hazard to target organs by a single exposure.

Issued: 2022-09-06 Version: 1.1 Page 5 of 7



Reference No:

Chronic Toxicity

Mutagenicity: This material has been classified as not a mutagen.

Carcinogenicity: This material has been classified as a Category 1A Hazard.

Reproductive toxicity (including via lactation): This material has been classified as not a reproductive toxicant.

Specific target organ toxicity (repeat exposure): This material has been classified as a Category 1 Hazard.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as not hazardous for acute aquatic exposure. Acute toxicity estimate (based on ingredients): > 100 mg/L

Long-term aquatic hazard: This material has been classified as not hazardous for chronic aquatic exposure. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log K_{ow} < 4.

Ecotoxicity: No information available.

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

Mobility: No data available.

13. DISPOSAL CONSIDERATIONS

Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)

The Stockholm Convention (Persistent Organic Pollutants)

Product Name: E3 Deep Pour & Xtreme Part C Aggregate

Issued: 2022-09-06 Version: 1.1 Page 6 of 7



The Rotterdam Convention (Prior Informed Consent)
Basel Convention (Hazardous Waste)
International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth): Unknown.

AICIS Status: All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC).

16. OTHER INFORMATION

Reason for issue: Minor Text Changes

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.

Product Name: E3 Deep Pour & Xtreme Part C Aggregate Reference No: Issued: 2022-09-06 Version: 1.1 Page 7 of 7